

DCS-F1622

1080P Hybrid Analogue Large Eyeball

Features

- 1/2.9" Sony Progressive Scan CMOS
- 2.8-12mm
- Full HD 1080P
- Video Transmission 300m
- IR Up to 35m
- 2D/3D DNR,dWDR,ICR,HLC,Mirror,Defog, Privacy Masking, Motion Detection
- Support AHD/TVI/CVI/CVBS Output
- IP66



Technical Specifications

| Camera | | General | |
|-------------------------|---|------------------------|-------------------------------|
| Image Sensor | • 1/2.9" Sony CMOS | Power Supply | • DC12V±10% |
| Signal System | • PAL/NTSC | Power Consumption | • 4W(Max) |
| Min. illumination | • Color:0.01Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON) | Operating Temperature | • -10°C ~ 55°C (14°F ~ 131°F) |
| S/N Ratio | • ≥50dB | Operating Humidity | • 0% - 85% RH |
| Day & Night | • ICR | Ingress Protection | • IP66 |
| Shutter Speed | • PAL:1/50-1/50000 NTSC:1/60-1/60000 | Approvals | • CE / FCC |
| Wide Dynamic Range | • dWDR | Material | • Aluminium Alloy |
| Digital Noise Reduction | • 2D/3D | Product Dimensions | • φ119x100mm |
| Lens | • 2.8-12mm | Product Weight | • 650g |
| FOV | • 85° | Video Output | |
| IR LED | • 24pcs | Max Distance | • 75-5 300m |
| IR Wavelength | • 850nm | Video Output | • AHD/TVI/CVI/CVBS |
| IR Range | • Up to 35m | Dimensions (mm) | |
| OSD Joystick | • Optional | | |
| Up the Coax | • Support | | |
| Image | | | |
| Effective Resolution | • 1920x1080 | | |
| Frame | • PAL:25fps ,NTSC:30fps | | |
| Mirror | • Support | | |
| Defog | • Support | | |
| HLC | • Support | | |
| Private Masking | • Support | | |
| Motion Detection | • Support | | |