

DCS-F1712

1080P Hybrid Analogue Bullet

Features

- 1/2.7" Progressive Scan CMOS
- 3.6mm
- Full HD 1080P
- Video Transmission 300m
- IR Up to 20m
- 2D DNR, dWDR, ICR
- Support AHD/TVI/CVI/CVBS Output
- IP66



Technical Specifications

| Camera | | General | |
|-------------------------|---|------------------------|-------------------------------|
| Image Sensor | • 1/2.7" CMOS | Power Supply | • DC12V±10% |
| Signal System | • PAL/NTSC | Power Consumption | • 3.5W(Max) |
| Min. illumination | • Color:0.05Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON) | Operating Temperature | • -10°C ~ 55°C (14°F ~ 131°F) |
| S/N Ratio | • ≥50dB | Operating Humidity | • 0% - 85% RH |
| Day & Night | • ICR | Ingress Protection | • IP66 |
| Shutter Speed | PAL:1/50-1/50000, NTSC:1/60-1/60000 | Approvals | • CE / FCC |
| Wide Dynamic Range | • dWDR | Material | • Aluminium Alloy |
| Digital Noise Reduction | • 2D | Product Dimensions | • Φ176×60mm |
| Lens | • 3.6mm | Product Weight | • 300g |
| FOV | • 85° | Video Output | |
| IR LED | • 18pcs | Max Distance | • 75-5 300m |
| IR Wavelength | • 850nm | Video Output | • AHD/TVI/CVI/CVBS |
| IR Range | • Up to 20m | Dimensions (mm) | |
| Support | • Support | | |
| Image | | | |
| Effective Resolution | • 1920x1080 | | |
| Frame | • PAL:25fps ,NTSC:30fps | | |
| Mirror | • N/A | | |
| Defog | • N/A | | |
| HLC | • N/A | | |
| Private Masking | • N/A | | |
| Mostion Detection | • N/A | | |